RAVAS-4100


Pallet truck scale with extended scale functions













RAVAS-4100

FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic and manual tare
- Totalling with sequence number
- Code entry (5-digit)
- Piece counting by sampling
- Piece counting by entry of piece weight
- Two RS232 outputs
- Internal clock
- Error messages in display
- Automatic switch-off after 30 minutes of non-use
- kg/lb toggle

STANDARD SPECIFICATIONS

Weighing capacity

Graduation

2.200 kg

200 - 500 kg: graduation 0.5 kg

500 - 2,200 kg: graduation 1 kg

Max. tolerance Display

Keypad 5 function keys, on/off key

Protection class load cells IP67, indicator IP65

35 hours, low battery indication

230V/12Vdc - 300 mA Charger

Charging time

Steering wheels

Loading wheels

Colour

Battery

Battery life

Own weight

Pump

multirange:

0 - 200 kg: graduation 0.2 kg

0.1% of the load lifted

LCD, digit height 18 mm, backlight

12Vdc/1.2Ah, exchangeable;

battery charger included

approximately 6 hours

rubber


polyurethane, single

red (RAL 3000), epoxy painted

99 kg

quick lift

DIMENSIONS IN MM



В	Fork width	170
С	Minimum fork height	87
	Space underneath fork	
D	Maximum fork height	205
	Lifting height	120
Ε	Width over forks	540
F	Height to top indicator	770

A Fork length







1150

PREMIUM OPTIONS*

- Extra exchangeable battery pack
- Built-in thermal printer
- Bluetooth or WLAN output
- Relay setpoint switch for automatic dosing

OPTIONS*

- Multirange graduation 0.1/0.2/0.5 kg
- Stainless steel fork shoes
- Stainless steel or galvanized truck
- Pivoting indicator: readout from all angles during dosing
- Footbrake or handbrake
- Different fork dimensions
- Different steering or loading wheels

* The use of options may change related specifications

RAVAS Europe B.V.

P.O. Box 2023, NL-5300 CA Zaltbommel, The Netherlands T. +31 (0)418 51 52 20, F. +31 (0)418 51 53 20 backoffice@ravas.com, www.ravas.com



IS LFT RAVAS-4100 EN EU rev.12.03.19 Changes reserver